



Lightning & Surge Protection Systems  
Designers, Manufacturers and Consultants  
HIGH PERFORMANCE ELECTRICAL SURGE PROTECTION™



## **ENERGUARD™** **RLI-40-2** **SPECIFICATIONS**

Nominal Operating Voltage.....	120/240 Split Phase
Maximum Continuous Operating Voltage.....	150/300 vac
Rated Current Per Phase [8/20ns].....	40ka
Rated Current Total.....	80ka
Energy Rating per Phase.....	680 Joules
Energy Rating Total.....	1360 Joules
Suppression Voltage L-N [@ 200 amps].....	350vp
Suppression Voltage L-N [@ 2000 amps].....	425vp
Operating Temperature Range.....	-40° to + 80°c
Humidity Tolerance [non condensing].....	< 95% R.H.
Front Panel Power Indicators.....	LEDS
Size.....	6 x 4 x 3 inches
Housing.....	Neema/ Eemac Type 1
Weight.....	5 Lbs.
CSA approved .....	LR47033

Connection is made via 12 AWG Stranded Tinned Copper Wire.

**TOLL FREE PHONE 1-888-596-2020 FAX 1-888-866-7775**  
**www.lightningtvss.com wilcan@lightningtvss.com www.powersurges.com**  
**8560 Torbram Road Units 34 & 35 Brampton, Ontario, Canada L6T 5C9**