



Lightning & Surge Protection Systems
Designers, Manufacturers and Consultants
HIGH PERFORMANCE ELECTRICAL SURGE PROTECTION™



ENERGUARD™ **RLI-40-3** **SPECIFICATIONS**

Nominal Operating Voltage.....	120/208 3 Phase
Maximum Continuous Operating Voltage.....	150/300 vac
Rated Current Per Phase [8/20ns].....	40ka
Rated Current Total.....	120ka
Energy Rating per Phase.....	680 Joules
Energy Rating Total.....	2040 Joules
Suppression Voltage L-N [@ 200 amps].....	350vp
Suppression Voltage L-N [@ 2000 amps].....	425vp
Operating Temperature Range.....	-40° to + 80°c
Humidity Tolerance [non condensing].....	< 95% R.H.
Front Panel Power Indicators.....	LEDS
Size.....	6 x 4 x 3 inches
Housing.....	Neema/ Eemac Type 1
Weight.....	5 Lbs.
CSA approved	LR47033

Connection is made via 12 AWG Stranded Tinned Copper Wire.

TOLL FREE PHONE 1-888-596-2020 FAX 1-888-866-7775
www.lightningvss.com wilcan@lightningvss.com www.powersurges.com
8560 Torbram Road Units 34 & 35 Brampton, Ontario, Canada L6T 5C9